


1/71



2/71




FIG. 2

Title: REFRIGERATOR SYSTEM AND SOFTWARE
ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070




FIG. 3

4/71




FIG. 4

5/71




FIG. 5




FIG. 6

6/71




FIG. 7

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
 Suite 2600, St. Louis, MO 63102 (314) 621-5070




FIG. 8



ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070

9/71

← TO
FIG 9A




FIG. 9B

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070

10/71




FIG. 10

11/71




FIG. 11

12/71





FIG. 12

13/71



Initialization: Shuts off heater and turns on fan. This mode is implemented so that the customer interface LED that is wired in parallel with the fan will turn on as soon as the button is hit. Time ti is the initialization time and will typically be approximately one minute.

Pos. Dampers: This state shuts off the fan, sets the single damper open then closes the dual damper. It then turns the fan back on. This is done for power management

PreHeat: This state regulates the pan temperature

LowHeat

HighHeat:

Terminate: This mode closes both dampers and shuts off the fan then returns to idle.

FIG. 13

14/71




FIG. 14

ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070

15/71





FIG. 15



TO --->
FIG 16B

FIG. 16A

16/71




FIG. 16B

Title: REFRIGERATOR SYSTEM AND SOFTWARE
ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070






FIG. 17

18/71




19/71

TO
 FIG 18A



Sealed System Behavior Diagram
 FIG. 18B


20/71



Fresh Food Fan Behavior Diagram

FIG. 19

21/71



Dispenser Behavior

FIG. 20A

23/71

486





FIG. 21

24/71



**John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070**

25/71





FIG. 23

26/71







FIG. 25


Temperature Setting Interaction Diagrams


28/71


FIG. 26




29/71







32/71



Door Open Interaction Diagram

FIG. 30

33/71





FIG. 31



Dispenser Control Algorithm

FIG. 32

35/71




FIG. 33

Defrost Control State Diagram

36/71





FIG. 34

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070



- Notes:**
1. The FF & Evaporator fans will shut off for the first five minutes that the door is open
 2. Only one fan at a time can be on at a time during diagnostics.
 3. Once the fan has been switched to high speed, it remains in that state until the operational cycle is complete.

FIG. 35

REFRIGERATOR SYSTEM AND SOFTWARE
ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070




FIG. 36

39/71






FIG. 37

40/71



41/71
 SENSOR READ AND ROLLING AVERAGE ALGO: 522



NOTE:
 Sensor Reading Algorithm
 Fresh food average uses this algorithm twice to create a 2nd pole filter.

FIG. 39






FIG. 40

42/71

Note: Any Routine is allowed to read a data store
 The command processor can read or write
 any data store.
 Dashed line indicates a path for initialization only

FIG. 41A








FIG. 42




FIG. 43

45/71




FIG. 44A

46/71






FIG. 44B

Title: REFRIGERATOR SYSTEM AND SOFTWARE
ARCHITECTUREJohn S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070


48/71

FIG. 45B



ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070



Title: REFRIGERATOR SYSTEM AND SOFTWARE
ARCHITECTURE

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070




FIG. 45D

51/71





FIG. 45E

52/71



John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
 Suite 2600, St. Louis, MO 63102 (314) 621-5070

53/71




FIG. 45G

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
 Suite 2600, St. Louis, MO 63102 (314) 621-5070







FIG. 46A

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070





John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
Suite 2600, St. Louis, MO 63102 (314) 621-5070



58/71






FIG. 47A

John S. Beulick, Armstrong Teasdale LLP, One Metropolitan Square,
 Suite 2600, St. Louis, MO 63102 (314) 621-5070





62/71





FIG. 48






FIG. 50




FIG. 51



66/71




FIG. 53

67/71




FIG. 54




FIG. 55





FIG. 56

69/71



COMPRESSOR ON?

$T1 \geq T1 \text{ MAX}$

SET DIVERTER FOR EQUAL AIR FLOW
TURN COMPRESSOR AND FANS ON
SET CONDITION 1 FLAG
SET $T2 \text{ ON} = T2$

$T2 \geq T2 \text{ MAX}$

SET DIVERTER FOR EQUAL AIR FLOW
TURN COMPRESSOR AND FANS ON
SET CONDITION 2 FLAG
SET $T1 \text{ ON} = T1$

FIG. 57

70/71




FIG. 58

71/71

